Claims

1. A method for automatically compensating for an unbalance correction position and an unbalance correction amount in a balancing machine, comprising:

5   an unbalance testing procedure for measuring an unbalance amount and an unbalance position of a rotor completing a primary unbalance correction thereof;

an initial unbalance amount determining procedure for determining whether or not an initial unbalance amount

10 present before the unbalance correction is not more than a predetermined value corresponding to an unbalance amount correctable by a one-time correction;

a counting procedure for incrementing a counted value when it is determined in the initial unbalance amount

15 determining procedure that the initial unbalance amount is not more than the predetermined value;

a good-quality determining procedure for determining whether or not the unbalance amount measured in the unbalance testing procedure is more than a reference value

20 for determining whether or not the rotor has a good quality;

an angular deviation measuring procedure for measuring an angular deviation between an unbalance position before the unbalance correction and the unbalance

25 position after the unbalance correction when it is

determined in the good-quality determining procedure that

the measured unbalance amount is more than the good-quality

reference value;

an angular deviation range determining procedure for

5 determining whether the angular deviation of the unbalance

position measured in the angular deviation measuring

procedure is within a range of $0°±X1°$ ($0 < X1 < 5$), a range

of $180°±X1°$, a range of $0°+X2°$ ($X1 < X2 < 90$), a range of

$180°+X2°$, a range $0°-X2°$, or a range of $180°-X2°$; and

10   an unbalance correction position and amount

compensating procedure for, when the counted value reaches

a predetermined value for calculation of an average value,

comparing the number of times when the angular deviation of

the unbalance position is within the range of $0°+X2°$ or

15 $180°+X2°$ with the number of times when the angular

deviation of the unbalance position is within the range of

$0°-X2°$ or $180°-X2°$, angularly compensating for the

unbalance correction position based on the angular

deviation of the unbalance position associated with a

20 higher-number one of the compared ranges, comparing the

number of times when the angular deviation of the unbalance

position is within the range of $0°±X1°$ in accordance with

an insufficient unbalance correction at an accurate

correction position with the number of times when the

25 angular deviation of the unbalance position is within the

51

range of 180°±X1° in accordance with an excessive unbalance

correction at an accurate correction position, and

compensating for the unbalance correction amount in

accordance with a higher-number one of the ranges of 0°±X1°

5   and 180°±X1° to increase the unbalance correction amount

when the higher-number range is 0°±X1° while reducing the

unbalance correction amount when the higher-number range is

180°±X1°.

10   2. The method according to claim 1, wherein it is

determined in the good-quality determining procedure

whether or not the rotor has a good quality, based on a

value obtained by deducting, from the good-quality

reference value, a value optionally set for an improvement

15   in the accuracy of a cutting depth for the unbalance

correction.

         3. The method according to claim 1, further

comprising:

20   a correction amount re-setting procedure for dividing

a unbalance amount range measurable prior to the unbalance

correction into a plurality of sub-ranges, executing the

unbalance testing procedure through the angular deviation

range determining procedure for each of the unbalance

25   amount sub-ranges to compare the number of times when the

angular deviation of the unbalance position is within the range of $0°\pm X1°$ with the number of times when the angular deviation of the unbalance position is within the range of $180°\pm X1°$, and re-setting an unbalance correction amount for

5   the unbalance amount sub-range in accordance with a higher-number one of the ranges of $0°\pm X1°$ and $180°\pm X1°$.

    4.   The method according to claim 1, further comprising:

10   a procedure for displaying a current condition of the balancing machine including a finally determined unbalance position error range, a rate of products having a good quality, and a correction amount error; and

        a procedure for automatically stopping an operation

15 of the balancing machine in accordance with a self determination of the balancing machine when a current machine condition value reaches a predetermined value at which it is impossible for the balancing machine to operate, and warning an operator of the current machine

20 condition.

    5.   The method according to claim 1, wherein the compensation for the unbalance correction position in the unbalance correction position and amount compensating

53

procedure is carried out by correcting only the unbalance correction amount.

6. The method according to claim 1, wherein the
5   compensation for the unbalance correction position in the unbalance correction position and amount compensating procedure is carried out by correcting both the unbalance correction position and the unbalance correction amount based on a value obtained by vector-calculating the
10 measured unbalance position and unbalance amount.

7. The method according to claim 1, wherein the compensation for the unbalance correction position in the unbalance correction position and amount compensating
15 procedure is carried out by repeatedly performing the unbalance correction under condition in which the unbalance correction position is optionally shifted with reference to 0° or 180°, storing a correction rate at every unbalance correction, calculating a maximum one of stored correction
20 rates, and correcting the unbalance correction position based on the calculated maximum correction rate.

8. The method according to claim 1, further comprising:

54

a basic data storing procedure for storing, as basic data, cutting data exhibiting a predetermined high correction rate or more so that the basic data is used as recovery data when a degradation in correction rate occurs.

5

9. The method according to claim 8, further comprising:

an automatic basic data recovering procedure for automatically recovering the stored basic data as cutting data when the correction rate is reduced to a predetermined value.